

SUBMITTAL SHEET

LASCO HEAVY TURF DOUBLE SWING TEE



| | |
|-----------------------|--|
| JOB NAME | |
| JOB LOCATION | |
| ENGINEER | |
| CONTRACTOR | |
| TAG | |
| PO NUMBER | |
| REPRESENTATIVE | |
| WHOLESALE DISTRIBUTOR | |

The Double Swing Tee has 1½" ACME thread on all connections and makes it possible to use two (2) Swing Joints from one (1) mainline connection. Use LASCO's "M" Inlet to connect to 1", 1¼" or 1½" Swing Joints. 315 psi rated by ASTM F-1970.



SPECIFICATIONS:

Maximum Working Pressure: 315 psi @ 73 deg F (Swing Joint)
ASTM 1970 - Standard Specification for Special Engineered Fittings, Appurtenances or Valves for use in Poly (Vinyl Chloride) (PVC) or Chlorinated Poly (Vinyl Chloride) (CPVC) Systems.
ASTM D1784 - Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly Vinyl Chloride (CPVC) Compounds.
ASTM F2768-09 - Standard Specification for Modified Stub ACME Thread Joint with Elastomeric Seal.

SUGGESTED SPECIFICATION:

All Swing joint rotating components are to be connected with ACME threads and O-Ring Seals in accordance with ASTM F2768-09.

MATERIALS:

PVC Type 1 Cell Classification 12454-B

HOW TO ORDER:

| Part No. | Ctn Qty |
|----------|---------|
| 305-015 | 10 |

USE LASCO STANDARD SWING JOINT INLET FITTINGS TO CONNECT TO MAINLINE / SERVICE FITTING: *(Inlet Fittings Sold Separately)*

| | |
|-------------------|--------------------------|
| ACME (G330-000) | Metric Spigot (G350-000) |
| Socket (G310-000) | Spigot-short (G320-000) |
| BSPT (G360-000) | Spigot-long (G370-000) |
| MIPT (G330-000) | |

WARRANTY:

Five Year Limited Performance Warranty
 LASCO® Fittings, Inc., an Aalberts company, extends to installing purchaser/contractors (and, through them, to the owners of irrigation systems) a Limited Five-Year Performance Warranty on all LASCO swing joints. LASCO Swing Joints and their individual component parts will be free from defects in materials, workmanship and assembly techniques that affect the performance of the units in professionally-designed irrigation systems. The Swing Joints will not leak when properly installed. The Swing Joints will not rot, rust, or corrode by electrolytic action.

WHAT IS NOT WARRANTED:

Damages or performance failures, including leakage, resulting from improper handling, storage or installation, from disassembly, modification, accident, vandalism or other events beyond control of the manufacturer; Installation in irrigation systems not in accordance with established professional standards; Consequential and associated damages to irrigation systems and to the properties in which they are installed, including, but not limited to labor and freight costs.

DURATION OF WARRANTY:

This warranty becomes effective on the date of shipment to the installing purchaser/contractor by LASCO or its authorized distributor/dealers; it remains in force for no less than Five (5) years.

414 Morgan Street • Brownsville, TN 38012
 (731) 772-3180 | www.lascofittings.com