



- ① FINISHED GRADE.
- ② VALVE BOX.
- ③ REMOTE CONTROL ZONE VALVE.
- ④ TEE 2" - LASCO ISO CONNECTOR FITTING, MODEL # 302-020.
- ⑤ ELBOW 90°, (2) TWO REQUIRED - 2", (FEMALE ACME x FEMALE ACME), LASCO MODEL, #308-020.
- ⑥ NIPPLE PVC SCH 80 BLANK BOTH ENDS, (3) REQ'D, 1 HIDDEN.
- ⑦ MALE - ACME ADAPTER 2", (5) FIVE, REQUIRED, LASCO MODEL # 336-020. THIS MALE ADAPTER HAS 2" MALE ACME THREADS x 2" SLIP SOCKET.
- ⑧ IRRIGATION PVC MAINLINE PIPE.
- ⑨ IRRIGATION PVC LATERAL LINE PIPE.
- ⑩ NIPPLE, (2) TWO REQUIRED, THREAD ONE END, (LASCO) LENGTH AS REQUIRED.
- ⑪ ELBOW 45°, (SLIP x SLIP), LASCO SURGE GUARD MODEL# 317-020

NOTES: INSTALL LASCO, 45° DEGREE ELBOWS, DOWN STREAM OF THE VALVE TO ACHIEVE CORRECT DEPTH, SIZE PER PLAN AND/OR THE VALVE OUTLET, (2) REQUIRED. USE A NON-HARDENING PIPE SEALANT W/O PTFE ON NPT THREADED CONNECTIONS.

00

LASCO ISOZONE CONNECTORS WITH R.C. VALVE

N.T.S. REMOTE CONTROL VALVE – SEE SEE LEGEND FOR MORE INFORMATION, SIZE PER PLAN.

DETAIL-FILE