




Slip x Spigot

UltraFix™ Compact Repair Coupling					
Part No	Size (in)	Ctn Qty	Code	List Price	
CUF-005	1/2	36	15	4.52	
CUF-007	3/4	24	15	5.05	
CUF-010	1	18	15	5.95	
CUF-012	1 1/4	12	15	11.07	
CUF-015	1 1/2	12	15	12.00	
CUF-020	2	8	15	18.67	
CUF-025	2 1/2	4	15	30.02	
CUF-030	3	3	15	37.56	
CUF-040	4	2	15	65.68	
CUF-060	6	1	15	179.34	

- Compact Design for tight places
- Dual EPDM O-rings
- Seals throughout pistons full travel
- Can be used as an Expansion Joint
- NSF Certified
- Working Pressure - 235 psi @ 73°F

LASCotite™



Duplex Seal – Compressive action of thread cap creates high concentrated pressure at two points illustrated. Since cap and body are recessed for compression sealing gasket, no fluid can enter thread cavity of cap.

Gripping Area – Compressive action creates strong gripping action over a wide area of pipe resisting longitudinal pull out.

Repairs or alterations in pipelines are simple with LASCotite fittings. Couplings can be inserted quickly between butted pipe ends. No clearance room is needed – simply slip a coupling all the way over one pipe end, realign the ends, center the coupling and tighten the nuts. New branch lines, test hookups, service joints, or temporary piping can be added easily. The LASCotite fittings can be removed and reused.

No threading or solvent cementing is required. The gaskets provide a positive, leak-proof compression seal. LASCotite fittings can be used to join iron pipe size plastic, steel or copper pipe and to attach plastic pipe to threaded valves or fittings.

LASCotite wall thicknesses meet or exceed those of Schedule 40 fittings as listed in ASTM D-2466.

SPECIFICATIONS:

All LASCotite fittings are produced from PVC Type I, Cell Classification 12454-B. LASCotite fittings comply fully with ASTM D-1784.

IMPORTANT:

- Restrain all pipe movement.
- Not to be used above ground.
- Do not use LASCotite fittings for compressed air or gas.
- Do not test PVC piping systems with compressed air or gas.
- Do not use fittings with liquids not recommended by LASCotite.
- Modifications of fittings voids the warranty.



Gasket x Gasket

LASCotite Coupling					
Part No	Size (in)	Working Pressure (psi)	Ctn Qty	Code	List Price
21123	1/2	315	30	14	4.69
21124	3/4	315	30	14	6.27
21125	1	315	20	14	8.13
21126	1 1/4	250	10	14	12.39
21127	1 1/2	250	10	14	12.64
21128	2	200	10	14	16.75
21129	2 1/2	200	8	14	31.24
21130	3	150	5	14	40.80
21131	4	150	6	14	67.19
21133	6	150	4	14	123.41



MPT x Gasket

LASCotite Male Adapter					
Part No	Size (in)	Working Pressure (psi)	Ctn Qty	Code	List Price
21303	1/2	315	30	14	3.92
21304	3/4	315	30	14	4.38
21305	1	315	20	14	5.61
21306	1 1/4	250	10	14	8.79
21307	1 1/2	250	10	14	9.67
21308	2	200	10	14	12.18

LASCotite Gaskets			
Part No	Size (in)	Code	List Price
22003	1/2	14	0.80
22004	3/4	14	0.96
22005	1	14	1.20
22006	1 1/4	14	1.57
22007	1 1/2	14	1.87
22008	2	14	2.26
22009	2 1/2	14	4.32
22010	3	14	9.34
22011	4	14	16.51
22013	6	14	17.08